



## DTP790 BATTERY TESTER



### Overview

#### DTP790 BATTERY TESTER

cod. 804245

Digital tester to check the status of the battery, the starting efficiency (CCA), the starter system and the alternator circuit of the vehicle.

Selectable reference international standards for vehicles to which the various starting amp ranges used by the battery manufacturer correspond.

Practical and compact, it allows operation on 12V batteries (WET, GEL, MF, AGM, PbCa, EFB) both disconnected and connected to the vehicle, facilitating testing operations which are rapid and easy to carry out.











The backlit LCD screen facilitates data reading, even in poorly lit environments.

Equipped with a built-in printer to print reports.

#### Features:

- for WET, GEL, MF, AGM, PbCa, EFB batteries from 4-250 Ah at 12V;
- tests carried out: battery status, starting efficiency (CCA), starting system, alternator circuit of the vehicle;
- selectable reference standard for the vehicle;
- tests can be carried out with battery disconnected or connected to the vehicle;
- backlit LCD display;
- multilingual: EN, IT, FR, DE, ES, NL;
- direct printing of reports using built-in printer.

### Technical data

 CODE	CODE 804245	 CURRENT RANGE 100/1400-IEC-DIN A	 OPERATING TEMPERATURE (MIN-MAX) 0 - 40 $\ddot{A}$ , $\ddot{A}$ °C
 CHARGING VOLTAGE 12 V		 CURRENT RANGE 100/2000-CA(MCA) A	 DIMENSIONS 9,8 x 7,8 x 27,5 cm
 BATTERY CAPACITY 4-250 Ah		 CURRENT RANGE 26A17/245H2-JIS A	 WEIGHT 0,714 kg
 CURRENT RANGE 100/2000-EN-SAE- CCA-BCI A			